




# GRANUFLEX®

## CONSTRUCTION

An aerial photograph of a modern, multi-story building with a large rooftop garden. The garden is lush with various plants, trees, and walkways. The building has a glass facade and a dark roof. The text "Circular construction, with rubber" is overlaid in white on the lower part of the image.

**Circular construction,  
with rubber**

A close-up photograph of a red rubber tile floor. The tiles are square and arranged in a grid pattern. A metal railing is visible in the upper left corner.

Recycled rubber is circular and it can be used to dampen sound and absorb shocks and vibrations. It is also non-slip, has good drainage properties and boasts a particularly long life. These are all reasons that make Granuflex products eminently suited to meet the demanding requirements of the construction industry. Moreover, our rubber tiles, mats and rolls are also impervious to the effects of moisture, sunlight and frost, making them well-suited to both indoor and outdoor use.

### ROOF/TERRACE TILE 30MM

Tile with an open structure to give optimal drainage. Can be used on roofs/balconies in areas away from the coast. Without pin/hole connection.

500x500MM | 1,000x1,000MM  
222ZWA030AA050XX



### ROOF/TERRACE TILE 40MM

Tile with an open structure to give optimal drainage. Can be used on roofs/balconies in areas away from the coast. Without pin/hole connection.

500x500MM | 1,000x1,000MM  
222ZWA040AA050XX



### ROOF/TERRACE TILE 80MM

Tile with an open structure to give optimal drainage. Can be used on roofs in coastal areas. Without pin/hole connection.

1,000x1,000MM  
222ZWA080AA100XX



### ROOF/TERRACE TILE PIN/HOLE 30MM

Tile with a more open structure to give optimal drainage. With pin/hole connection for easy installation.

500x500MM  
222ZWA030M3050XX



### HALF ROOF/TERRACE TILE PIN/HOLE 30MM

Tile with a more open structure to give optimal drainage. With pin/hole connection for easy installation.

500x250MM  
222ZWA030M3S25XX



### ARTIFICIAL GRASS TERRACE TILE NATURAL LOOK 50MM

Tile with a long-fibred artificial grass top layer. Without pin/hole connection. Its high quality artificial grass lends it a very natural appearance.

500x500MM  
230KGR030B4050ET



### TILE SUPPORT 10MM

Tile supports are typically used to protect the bituminous layer on roof terraces/gardens and flat roofs. They are the perfect solution for supporting stone or concrete tiles. Packaged per 144 pieces.

100x100MM  
(Andere maten verkrijgbaar op aanvraag)  
228ZWA010AA100GR



### OPTI-DRAIN DRAINAGE MAT

A mat that is used to control drainage and is available in both horizontal and vertical configurations. Equipped with a handy interlocking system and geo-textile layer.

20,000x1,200MM  
230ZWA009HD120XX



### CHARACTERISTICS



DRAINAGE



TESTED FOR WIND LOAD



ANTI-SLIP



SUSTAINABLE

### COLOURS



BLACK



GREY



GREEN



RED

### GUARANTEE

3 YEARS

### CERTIFICATION

FIRE CLASSIFICATION EN 13501

WIND LOAD

